

- 1. Unique identification code of the product type :**
Dry Pressed Ceramic Porcelain Tile, with water absorption $E_b \leq 0,5 \%$
- 2. Intended use(s) :** For internal and external wall and floor covering
- 3. Name or registered trade mark, and contact address of the manufacturer :**
Kaleseramik Çanakkale Kalebodur Seramik San. A.Ş. 17400 Çan/Çanakkale
- 4. System(s) of assessment and verification of constancy of performance (AVCP) :** System 4
- 5. Name and identification number of notified laboratory :** Not applicable
- 6. Declared performances**

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 _{FL}	EN 14411:2012
Release of dangerous substance, for:		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	>1300 N	
Slipperiness	See table attached	
Tactility	NPD	
Bond strength/adhesion, for:		
Cementitious adhesive, type C1	>1,0 N/mm ²	
Dispersion adhesives, type D2	>2,0 N/mm ²	
Reaction resin adhesives, type R2	>1,0 N/mm ²	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Place: Çan/Çanakkale

Date: 31.05.2013

Name: Alper ÖZKÖK

Function: Quality Management and Control Manager

Kaleseramik Çanakkale Kalebodur Seramik Sanayi A.Ş.

Merkez: Büyükdere Cad. Kaleseramik Binası 34330 Levent - İstanbul - T 0212 371 5253 - F 0212 270 6551

Fabrikalar: 17430 Çan - Çanakkale - T 0286 416 1717 - 416 1911 - F 0286 416 1741 - 416 1916

İst. Tic. Sicil: 71314/8352 Büyük Mükellefler V.D. 2290004296 kale.com.tr


Kaleseramik
Çanakkale Kalebodur
Seramik San.A.Ş.